

## Waveguide E-Bend

0.762±0.03

1.1 1.2			
12	Waveguide type	WR15	
—	Flange type	FUGP620 (UG385/U)	
1.3	Finish	Gold plating	
1.4	Material	Copper/Brass	
1.5	Dimension	A=20 mm, B=20 mm	
2.0	Electrical Specifications		
2.1	Frequency Range	50-75 GHz	
2.2	VSWR (Max)	1.15	
3.0	Outline Drawings		
	0.4X45°	2-Ø1.7*\text{\pi3} 0.38X45*\text{chawfers}\\ 4-Ø3.556X0.762\\ Countersinks	

FUGP620

Ø14.3



**Revision History** 

Date	Revision	Changes
25-Mar-2009	1	First release

Information furnished is believed to be accurate and reliable. However, Vector Telecom assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Vector Telecom. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. Vector Telecom products are not authorized for use as critical components in life support devices or systems without express written approval of Vector Telecom.

The Vector Telecom logo is a registered trademark of Vector Telecom Pty Ltd.

© 2006 Vector Telecom Pty Ltd - All rights reserved

Email: sales@vectortele.com

www.vectortele.com