

Waveguide Transition



Part No: VT620740WA50PPC

1.1 Waveguide type WR15 to WR12 1.2 Flange type FUGP620/FUGP740 1.3 Material Copper/Brass 1.4 Finish Gold plating 1.5 Length 50 mm 2.0 Electrical Specifications 60.5-75.8 GHz 2.1 Frequency range 60.5-75.8 GHz 2.2 VSWR (Max) 1.15 3.0 Outline Drawing Continue of the second s	1.0	Mechanical Specifications		
1.3 Material Copper/Brass 1.4 Finish Gold plating 1.5 Length 50 mm 2.0 Electrical Specifications 2.1 Frequency range 60.5-75.8 GHz 2.2 VSWR (Max) 1.15 3.0 Outline Drawing 1.4 Finish Solution Drawing Solution Drawing So	1.1	Waveguide type	WR15 to WR12	
1.4 Finish Gold plating 1.5 Length 50 mm 2.0 Electrical Specifications 2.1 2.1 Frequency range 60.5-75.8 GHz 2.2 VSWR (Max) 1.15 3.0 Outline Drawing	1.2	Flange type	FUGP620/FUGP740	
1.5 Length 50 mm 2.0 Electrical Specifications 2.1 Frequency range 60.5-75.8 GHz 2.2 VSWR (Max) 1.15 3.0 Outline Drawing Improve the second secon	1.3	Material	Copper/Brass	
2.0 Electrical Specifications 2.1 Frequency range 60.5-75.8 GHz 2.2 VSWR (Max) 1.15 3.0 Outline Drawing 4.73.3 FIGP620 4.73.3 FIGP620 4.73.3 Control of the second s	1.4	Finish	Gold plating	
2.1 Frequency range 60.5-75.8 GHz 2.2 VSWR (Max) 1.15 3.0 Outline Drawing 1.15	1.5	Length	50 mm	
2.1 Frequency range 60.5-75.8 GHz 2.2 VSWR (Max) 1.15 3.0 Outline Drawing 1.15				
2.2 VSWR (Max) 3.0 Outline Drawing	2.0	Electrical Specifications		
3.0 Outline Drawing	2.1	Frequency range	60.5-75.8 GHz	
$\frac{4.73}{50} + \frac{1000}{100} + 100$	2.2	VSWR (Max)	1.15	
$\frac{4.73}{50} + \frac{1000}{100} + 100$				
Image: constrained of the second of the s	3.0	Outline Drawing		
2.401.7 ^{1/8} 0.38X45' (Damfer) 440UNC-28 (Tapped) 4403.556X0.762 (Countersink) 55 0.762±0.03 6.35 6.35		2-0.4 × 0.762±0.0	30° 2-0.4 × 30° 3 0.762±0.03 50 2017 ¹⁰ 0.38745' (Chanfer) 400.NC-28 (Tapped) 400.NC-28 (Tapped)	
3.3 0.38X45" (Chanfer) 440UNC-28 (Tapped) 463.556X0.762 (Countersink) 463.556X0.762 (Countersink) 463.556X0.762 (Countersink) 463.556X0.762 (Countersink) 463.556X0.762 (Countersink) 463.556X0.762 (Countersink) 463.556X0.762 (Countersink) 463.556X0.762 (Countersink) 463.556X0.762 (Countersink)	2-01.7 ***			
		0.0245°	0.38X45° (Chauf er) 4-40UNC-28 (Tapped) 4-63.556X0.762 (Countersink) 4-63.556X0.762 (Countersink) 4-63.556X0.762 (Countersink) 4-63.556X0.762 (Countersink) 4-63.556X0.762 (Countersink) 4-63.556X0.762 (Countersink)	
FUGF/40			FUGP740	

Vector Telecom Pty Ltd Level 40, 140 William Street, Melbourne VIC 3000, Australia Tel: +61 3 9607 8357 - Fax: +61 3 9607 8282 - www.vectortele.com



Revision History

Date	Revision	Changes
26-Mar-2006	1	First release

Information furnished is believed to be accurate and reliable. However, Vector Telecom assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Vector Telecom. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. Vector Telecom products are not authorized for use as critical components in life support devices or systems without express written approval of Vector Telecom.

The Vector Telecom logo is a registered trademark of Vector Telecom Pty Ltd.

© 2006 Vector Telecom Pty Ltd - All rights reserved

Email: sales@vectortele.com

www.vectortele.com

Vector Telecom Pty Ltd

Level 40, 140 William Street, Melbourne VIC 3000, Australia Tel: +61 3 9607 8357 - Fax: +61 3 9607 8282 - www.vectortele.com