

## **Waveguide to Coaxial Adapter**

Part No: VT140WCANKPC

Mochanical Specifications		
	WDG2	
	WR62	
	N Female	
<u> </u>	FBP140 (Cover)	
	Copper/Brass	
	Silver plating	
Outside finish	3 71	
Operating Temperature	-30°C to +70°C	
•		
	11.9-18 GHz	
VSWR (Max)	1.25	
Insertion Loss (Max)	0.3 dB	
Power Handling 100 W (CW)		
Outline Descripes		
3.0   Outline Drawings   N-50K   4-84		
	Mechanical Specifications  Waveguide type Connector type Flange type Material Inside finish Outside finish Operating Temperature  Electrical Specifications Frequency range VSWR (Max) Insertion Loss (Max) Power Handling  Outline Drawings	



**Revision History** 

Date	Revision	Changes
23-Jun-2020	1	First release

Information furnished is believed to be accurate and reliable. However, Vector Telecom assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Vector Telecom. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. Vector Telecom products are not authorized for use as critical components in life support devices or systems without express written approval of Vector Telecom.

The Vector Telecom logo is a registered trademark of Vector Telecom Pty Ltd.

© 2006 Vector Telecom Pty Ltd - All rights reserved

Email: sales@vectortele.com

www.vectortele.com